


오링 규격표

오링규격 JIS B 2401 일본공업 표준규격 (P.G.V.S)

P 계열오링			G 계열오링		
부품번호	오링규격		부품번호	오링규격	
	ID	CS		ID	CS
P3	2.8	1.9	P71	70.6	5.7
P4	3.8	1.9	P75	74.6	5.7
P5	4.8	1.9	P80	79.6	5.7
P6	5.8	1.9	P85	84.6	5.7
P7	6.8	1.9	P90	89.6	5.7
P8	7.8	1.9	P95	94.6	5.7
P9	8.8	1.9	P100	99.6	5.7
P10	9.8	1.9	P102	101.6	5.7
P10A	9.8	2.4	P105	104.6	5.7
P11	10.8	2.4	P110	109.6	5.7
P11.2	11.0	2.4	P112	111.6	5.7
P12	11.8	2.4	P115	114.6	5.7
P12.5	12.3	2.4	P120	119.6	5.7
P14	13.8	2.4	P125	124.6	5.7
P15	14.8	2.4	P130	129.6	5.7
P16	15.8	2.4	P132	131.6	5.7
P18	17.8	2.4	P135	134.6	5.7
P20	19.8	2.4	P140	139.6	5.7
P21	20.8	2.4	P145	144.6	5.7
P22	21.8	2.4	P150	149.6	5.7
P22A	21.7	3.5	P150A	149.5	8.4
P22.4	22.1	3.5	P155	154.5	8.4
P24	23.7	3.5	P160	159.5	8.4
P25	24.7	3.5	P165	164.5	8.4
P25.5	25.2	3.5	P170	169.5	8.4
P26	25.7	3.5	P175	174.5	8.4
P28	27.7	3.5	P180	179.5	8.4
P29	28.7	3.5	P185	184.5	8.4
P29.5	29.2	3.5	P190	189.5	8.4
P30	29.7	3.5	P195	194.5	8.4
P31	30.7	3.5	P200	199.5	8.4
P31.5	31.2	3.5	P205	204.5	8.4
P32	31.7	3.5	P209	208.5	8.4
P34	33.7	3.5	P210	209.5	8.4
P35	34.7	3.5	P215	214.5	8.4
P35.5	35.2	3.5	P220	219.5	8.4
P36	35.7	3.5	P225	224.5	8.4
P38	37.7	3.5	P230	229.5	8.4
P39	38.7	3.5	P235	234.5	8.4
P40	39.7	3.5	P240	239.5	8.4
P41	40.7	3.5	P245	244.5	8.4
P42	41.7	3.5	P250	249.5	8.4
P44	43.7	3.5	P255	254.5	8.4
P45	44.7	3.5	P260	259.5	8.4
P46	45.7	3.5	P265	264.5	8.4
P48	47.7	3.5	P270	269.5	8.4
P49	48.7	3.5	P275	274.5	8.4
P50	49.7	3.5	P280	279.5	8.4
P48A	47.6	5.7	P285	284.5	8.4
P50A	49.6	5.7	P290	289.5	8.4
P52	51.6	5.7	P295	294.5	8.4
P53	52.6	5.7	P300	299.5	8.4
P55	54.6	5.7	P315	314.5	8.4
P56	55.6	5.7	P320	319.5	8.4
P58	57.6	5.7	P335	334.5	8.4
P60	59.6	5.7	P340	339.5	8.4
P62	61.6	5.7	P355	354.5	8.4
P63	62.6	5.7	P360	359.5	8.4
P65	64.6	5.7	P375	374.5	8.4
P67	66.6	5.7	P385	384.5	8.4
P70	69.6	5.7	P400	399.5	8.4



G 계열오링

부품번호	오링규격	
	ID	CS
G330	329.3	5.7
G335	334.3	5.7
G340	339.3	5.7
G345	344.3	5.7
G350	349.3	5.7
G355	354.3	5.7
G360	359.3	5.7
G354	364.3	5.7
G370	369.3	5.7
G375	374.3	5.7
G380	379.3	5.7
G385	384.3	5.7
G390	389.3	5.7
G395	394.3	5.7
G400	399.3	5.7

V 계열오링

부품번호	오링규격	
	ID	CS
V15	14.5	4.0
V24	23.5	4.0
V34	33.5	4.0
V40	39.5	4.0
V55	54.5	4.0
V70	69.0	4.0
V85	84.0	4.0
V100	99.0	4.0
V120	119.0	4.0
V150	148.5	4.0
V175	173.0	4.0
V225	222.5	6.0
V275	272.0	6.0
V325	321.5	6.0
V380	376.0	6.0
V430	425.5	6.0
V480	475.0	10.0
V530	524.5	10.0
V585	579.0	10.0
V640	633.5	10.0
V690	683.0	10.0
V740	732.5	10.0
V790	782.0	10.0
V845	836.5	10.0
V950	940.5	10.0
V1055	1044.0	10.0

S 계열오링

부품번호	오링규격		부품번호	오링규격		부품번호	오링규격		부품번호	오링규격	
	ID	CS		ID	CS		ID	CS		ID	CS
S-2	1.5	1.5	S-22.4	21.9	2.0	S-45	44.5	2.0	S-105	104.5	2.0
S-3	2.5	1.5	S-24	23.5	2.0	S-46	45.5	2.0	S-110	109.5	2.0
S-4	3.5	1.5	S-25	24.5	2.0	S-48	47.5	2.0	S-112	111.5	2.0
S-5	4.5	1.5	S-26	25.5	2.0	S-50	49.5	2.0	S-115	114.5	2.0
S-6	5.5	1.5	S-28	27.5	2.0	S-53	52.5	2.0	S-120	119.5	2.0
S-7	6.5	1.5	S-28	28.5	2.0	S-55	54.5	2.0	S-125	124.5	2.0
S-8	7.5	1.5	S-30	29.5	2.0	S-56	55.5	2.0	S-130	129.5	2.0
S-9	8.5	1.5	S-31.5	31.0	2.0	S-60	59.5	2.0	S-132	131.5	2.0
S-10	9.5	1.5	S-32	31.5	2.0	S-62	61.5	2.0	S-135	134.5	2.0
S-11	10.5	1.5	S-32.5	32.0	2.0	S-63	62.5	2.0	S-140	139.5	2.0
S-11.2	10.7	1.5	S-34	33.5	2.0	S-65	64.5	2.0	S-145	144.5	2.0
S-12	11.5	1.5	S-35	34.5	2.0	S-67	66.5	2.0	S-150	149.5	2.0
S-12.5	12.0	1.5	S-35.5	35.0	2.0	S-70	69.5	2.0	S-160	159.5	2.0
S-14	13.5	1.5	S-36	35.5	2.0	S-71	70.5	2.0	S-170	169.5	2.0
S-15	14.5	1.5	S-38	37.5	2.0	S-75	74.5	2.0	S-180	179.5	2.0
S-16	15.5	1.5	S-38.5	38.0	2.0	S-80	79.5	2.0	S-200	199.5	2.0
S-18	17.5	1.5	S-39	38.5	2.0	S-85	84.5	2.0	S-250	249.5	2.0
S-19	18.5	1.5	S-40	39.5	2.0	S-90	89.5	2.0	S-300	299.5	2.0
S-20	19.5	1.5	S-42	41.5	2.0	S-95	94.5	2.0			
S-22	21.5	1.5	S-44	43.5	2.0	S-100	99.5	2.0			